


**Yellow Pin Galvanised Alloy Pin Shackles to U.S. Federal Spec. RR-C-271D
Sizes 1/2T-25 T meet the Performance Requirements of ISO2415 Grade 6
Screw Pin Anchor (Bow) Shackles (G - 209)
Body finished Hot Dipped Grey Galvanised, with Yellow Pin**

CODE	SML (kg)	d (mm)	D (mm)	A (mm)	B (mm)	C (mm)
1007SA0060	500	6	8	13	20	28
1007SA0080	750	8	10	14	21	31
1007SA0100	1000	10	11	17	26	37
1007SA0110	1500	11	13	18	29	43
1007SA0130	2000	13	16	21	33	48
1007SA0160	3250	16	20	27	43	60
1007SA0200	4750	20	22	32	51	71
1007SA0220	6500	22	26	37	58	84
1007SA0260	8500	26	28	43	68	95
1007SA0280	9500	28	32	46	74	108
1007SA0320	12000	32	35	52	83	119
1007SA0350	13500	35	38	56	89	132
1007SA0380	17000	38	42	60	98	146
1007SA0440	25000	44	51	73	127	178



- Working load limit is permanently marked on every shackle. Forged, Quenched and Tempered, with alloy pins.
- Safety factor 6:1.